

b.) Amendments to the Specification

Amend the paragraph beginning on page 22, line 14 to read as follows:

"Examples of suitable containers which are also clean-burning, i.e., burning with 15 negligible smoke or odor, are the 4-6 oz size of injection molded polypropylene tubs (e.g., part numbers 451 and S651, Airlite Plastics Company; Omaha, NE, which are both made from plastics containing less than one percent of inorganic materials.). An example of a suitable alcohol fuel is: 70% by weight alcohol including 54% by weight ethanol, 16% isopropanol, 30% water, and 0.3% Carbopol®Ultrez 10 polyacrylate thickener (BFGoodrich Specialty Chemicals, Cleveland, OH), providing a kinematic viscosity of 15,000-30,000 cp. In other embodiments, the viscosity may be as low as 250 cp and as high as 100,000 cp, or even fully gelled."

selected from the group consisting of methanol, ethanol, isopropanol, n-propanol, and combinations thereof.

7. (Previously amended) The assembly of claim 39, wherein said alcohol-based fuel liquid comprises ethanol and at least 6% by weight isopropanol, wherein enhanced and sustained flame visibility is provided by the presence of said isopropanol in said fuel liquid.

8. (Previously amended) The assembly of claim 39, wherein said alcohol-based fuel liquid further comprises between 1% and 35% by weight water, wherein said water